

Scheduled Maintenance

Customer Name:	Model:	Plate number:
Frame number (VIN):	Registration date:	Mileage:
Current date:	Work Order Number:	Service type:

Scheduled Maintenance Check List for Superbike family

☒ ☒ Check the boxes close to the performed service operations

Performed	Replaced		Time Service*			
			Mileage Service DESMO*			
			Mileage Service OIL*			
			Mileage Service 1000*			
<input type="checkbox"/>		Read fault memory with the DDS 2.0 tester, and check technical updates and recall campaigns on DCS	•	•		12
	<input type="checkbox"/>	Change engine oil and filter	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check and clean air filter		•		12
	<input type="checkbox"/>	Change air filter			•	
	<input type="checkbox"/>	Replace timing belts (848, 1098 and 1198 only)			•	60
<input type="checkbox"/>		Check and/or adjust valve clearance (848, 1098 and 1198 only)		•	•	
<input type="checkbox"/>		Check and/or adjust valve clearance			•	
<input type="checkbox"/>	<input type="checkbox"/>	Check secondary air system reeds (where available)			•	
	<input type="checkbox"/>	Replace spark plugs			•	
	<input type="checkbox"/>	Change coolant			•	48
<input type="checkbox"/>		Reset the variable-length intake manifold system (VIS) using DDS 2.0 (Panigale V4 only)			•	
	<input type="checkbox"/>	Change front fork fluid				36
<input type="checkbox"/>	<input type="checkbox"/>	Visually check the front fork and rear shock absorber seals	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check clutch plate pack thickness (models with dry clutch only)			•	
	<input type="checkbox"/>	Replace clutch housing (models with dry clutch only)	Every 48,000km/30.000 mi			
<input type="checkbox"/>	<input type="checkbox"/>	Check brake and clutch fluid level	•	•		12
	<input type="checkbox"/>	Change brake and clutch fluid				24
<input type="checkbox"/>	<input type="checkbox"/>	Check front and rear brake disc and pad wear		•		12
<input type="checkbox"/>		Check the proper tightening of front and rear brake calliper screws and front brake disc screws		•		12
<input type="checkbox"/>		Check the tightening of the rear brake disc screws (with removal of rear wheel shaft if rear brake disc screws with hexagon wrench flat are present)			•	
<input type="checkbox"/>		Check front and rear wheel nuts and rear sprocket nut tightening		•		12
<input type="checkbox"/>		Check frame-to-engine, frame-to-swinging arm and frame-to-rear shock absorber fasteners tightening		•		12
<input type="checkbox"/>		Check tightening of RH tripod to rear bank fastener (Panigale V4 R only)			•	
<input type="checkbox"/>	<input type="checkbox"/>	Check the wheel hub bearings		•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check the cush drive damper on rear sprocket and lubricate the rear wheel shaft			•	
<input type="checkbox"/>		Check chain, rear sprocket and sprocket wear and check final drive chain tension, lubrication and stretch. Measured stretch value: _____ (mm) NOTE: It is recommended to change the final drive chain kit within 20,000 km/12,000 mi.	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check steering tube bearing clearance		•		12
<input type="checkbox"/>		Check the freedom of movement and tightening of the side stand	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check that all gaiters and visible hoses (i.e. fuel, brake and clutch, cooling system, bleed, drain hoses, etc.) are not cracked, are tight and properly housed	•	•		12
<input type="checkbox"/>		Check rear brake lever free play and handlebar lever and pedal control lubrication	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check tyre pressure and wear	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check the operation of all electric safety devices (side stand and clutch sensor, front and rear brake switch, engine stop switch, gear/neutral sensor)	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Check lighting devices, turn indicators, horn and controls operation	•	•		12
<input type="checkbox"/>	<input type="checkbox"/>	Adjust exhaust butterfly valve opening Bowden cable using DDS 2.0 (Panigale V4 only)	•	•		12
<input type="checkbox"/>		Final test and road test of the motorcycle, testing safety devices (e.g. ABS and DTC), electric fans and idling	•	•	•	12
<input type="checkbox"/>		Visually check the coolant level and circuit for damage	•	•	•	12
<input type="checkbox"/>		Soft cleaning of the vehicle, service coupon registration with turning off of Service warning light on instrument panel with DDS 2.0 and filling in of the on-board documentation (Service Booklet)	•	•	•	12

* The Mileage 1000 Service must be performed after the first 1,000km/600 mi.

The Mileage Service OIL must be performed every 12,000 km/7,500 mi for the model versions 848/1098/1198/899 Panigale/959 Panigale/1199 Panigale/1299 Panigale/Panigale V2/Panigale V4.

The Mileage Service DESMO must be performed every 24,000 km/15,000 mi for the model versions 848/1098/1198/899 Panigale/959 Panigale/1199 Panigale/1299 Panigale/Panigale V2/Panigale V4.

The Time Service must be performed every 12 months.

NOTE: For the models 848/1098/1198/899 Panigale/959 Panigale/1199 Panigale and 1299 Panigale in case of Mileage Service DESMO it is necessary to perform also a Mileage Service OIL .

Thank you! Your Ducati Technician: