



Check List for Scheduled Maintenance



Customer Name:	Model:	Plate number:
Frame number (VIN):	Registration date:	Mileage:
Current date:	Work Order Number:	Service type:

Scheduled Maintenance Check List for SuperSport family

☒ ☒ Check the boxes close to the performed service operations

Performed	Replaced		Annual Service 📅*			
			Desmo Service 🔧*			
			Oil Service 🛢️*			
			First Service 1000*			
☐	☐	Reading of the error memory with DDS 3.0 and check of technical updates and recall campaigns on DCS	•	•	•	12
☐	☐	Change engine oil and filter	•	•		12
☐	☐	Check and clean air filter		•		12
☐	☐	Change air filter			•	
☐	☐	Change timing belts			•	60
☐	☐	Check and/or adjust valve clearance			•	
☐	☐	Replace spark plugs			•	
☐	☐	Change coolant			•	48
☐	☐	Change front fork fluid	every 45,000km/27,000mi			
☐	☐	Visually check the front fork and rear shock absorber seals	•	•		12
☐	☐	Check brake and clutch fluid level (if present)	•	•		12
☐	☐	Change brake and clutch fluid (if present)				24
☐	☐	Check front and rear brake disc and pad wear		•		12
☐	☐	Check the proper tightening of brake calliper bolts, brake disc screws and front and rear wheel nuts		•		12
☐	☐	Check rear sprocket nut tightening		•		12
☐	☐	Check frame-to-engine, frame-to-swinging arm and frame-to-rear shock absorber fasteners tightening		•		12
☐	☐	Check the wheel hub bearings		•		12
☐	☐	Check silentbloks on rear sprocket and lubricate the rear wheel shaft			•	
☐	☐	Check chain, chain sliding shoes, front and rear sprockets wear and check final drive chain tension, lubrication and stretch. Measured slackening value: _____ (cm) NOTE: It is recommended to change the final drive chain kit within 20,000 km/12,000 mi.	•	•		12
☐	☐	Check steering tube bearing clearance		•		12
☐	☐	Check the freedom of movement and tightening of the side stand	•	•		12
☐	☐	Check that all gaiters and visible hoses (i.e. fuel, brake and clutch, cooling system, bleed, drain hoses, etc.) are not cracked, are tight and properly housed	•	•		12
☐	☐	Check rear brake lever free play and handlebar lever and pedal control lubrication	•	•		12
☐	☐	Check cable clutch lever free play (if present)	•	•		12
☐	☐	Check tyre pressure and wear	•	•		12
☐	☐	Check the operation of all electric safety devices (side stand and clutch sensor, front and rear brake switch, engine stop switch, gear/neutral sensor)	•	•		12
☐	☐	Check lighting devices, turn indicators, horn and controls operation	•	•		12
☐	☐	Final test and road test of the motorcycle, testing safety devices (e.g. ABS and DTC), electric fans and idling	•	•	•	12
☐	☐	Visually check the coolant level and circuit for damage	•	•	•	12
☐	☐	Softly clean the motorcycle	•	•	•	12
☐	☐	Service coupon registration with turning off of Service warning light on instrument panel with DDS 3.0 and filling in of the on-board documentation (Service Booklet)	•	•	•	12

* The First Service 1000 must be performed after the first 1,000 km/600 miles or within 6 months from delivery of motorcycle to Customer.
 The Oil Service 🛢️ must be performed every 15,000 km/9,000 mi.
 The Desmo Service 🔧 must be performed every 30,000 km/18,000 mi.
 The Annual Service 📅 must be performed every 12 months.

Thank you! Your Ducati Technician: